

Overexcitation rectifiers with adjustable holding voltage				
voltage / VAC tolerance: ±10%	48	110 – 120 / 220 - 230	380 - 415	460 - 525
max. current / ADC				
18 / 9	upon request	33 43312A03 - CE according to EMC directive - mounting on 35mm rail - adjustable overexcitation time - holding voltage adjustable - DC-side switching - powerless On/Off switching		
8 / 4		33 43311A03 - similar to 33 43312A03		
4 / 2		33 43310A03	33 43310A00	upon request
		- similar to 33 43312A03	- similar to 33 43312A03	
Overexcitation rectifiers based on full wave / half wave switching				
voltage / VAC tolerance: ±10%	48 - 120	220 - 415	460 - 525	
max. current / ADC				
6 / 3	32 17350E04/14/24 32 17150E04 32 17353E04	32 17350E00/10/20 32 17150E00 32 17353E00	32 17350E08/28	
	- CE according to EMC directive - mounting in motor terminal boxes (32 17350...) - mounting on 35mm rail (32 17353...) - mounting by PG screw fitting (32 17150...) - overexcitation time 0,25/1 and 1,8/3s (32 17150E.. only 0,25s) - DC side switching - moulded enclosure			
voltage / VAC tolerance: ±10%	48	110 – 230	220 – 415	460 - 525
max. current / ADC				
3 / 1,5	upon request	32 17221A03 - CE as per EMC directive - variable mounting especially for motors - compatible with rectifiers 32 x7x2xAxx - overexcitation time 0,3 – 1,3s		
		32 17320A03/23		
		- similar to 32 17221A03		
		- DC side switching allowed		
2 / 1			32 17221A00 - similar to 32 17221A03	
			32 17320A00	
			- similar to 32 17320A03	

Overexcitation Rectifiers - Dimensions (mm)

Overexcitation rectifiers with adjustable holding voltage							
voltage / VAC tolerance: ±10%		48	110 – 120 / 220 - 230		380 – 415	460 - 525	
max. load / ADC	18 / 9	upon request	33 43311A03				
	8 / 4		33 43311A03				
	4 / 2		33 43310A03		33 43310A00	upon request	
Overexcitation rectifiers based on full wave / half wave switching							
voltage / VAC tolerance: ±10%		48 - 120		220 - 415		460 - 525	
max. load / ADC	6 / 3	32 17350E04/14/24 32 17150E04 32 17353E04		32 17350E00/10/20 32 17150E00 32 17353E00		32 17350E08/28	
voltage / VAC tolerance: ±10%		48	110 – 230		220 – 415		460 - 525
max. load / ADC	3/1,5	upon request	32 17221A03 32 17320A03/23		32 17221A00 32 17320A00		
	2 / 1						